

CHEMAX[®] A-300

Boiler chemical

CHEMAX A-300 has a complete inhibiting effect on corrosion condensate water system.

The principal ingredients of CHEMAX A-300 are the selected amine inorganic alkaline which can inhibit the corrosion effectively at condensate tube and so on, and can minimize treatment cost.

-
- Dilute one part of CHEMAX A-300 with 10~20 parts of pure water or D.S.G feed water and feed it continuously by a metering pump into D.S.G feed water line or water stripper water feed line.

How to use

- The dosage shall be so adjusted that the condensate water pH will be above 9.0.
- General dosage will be 1 ~ 5ppm against feed water quantity.

-
- Appearance : Colorless or Light yellowish liquid

Properties

- Specific gravity : 0.99 ± 0.05
- pH (neat) : 12.9 ±1.0

-
- CHEMAX A-300 is strongly alkaline, the chemical storage tank, pipings, etc. shall not be made of copper or copper compound material. The tank shall probably be made of stainless steel.

Handling

- & ● Wear goggles and rubber gloves when handling.

Storage

- In case of skin contact wash thoroughly with water.
- If eyes are affected, flush with water and get medical attention.
- Do not use the empty containers for drinking water supply.

Packing

-
- 20kg/200kg PE Container
-

Official worldwide distributor



KOSMO E&T Co., Ltd.
 D715, Indeogwon IT Valley, 653, Poil-dong, Uiwang-si, Gyeonggi-do, #437-120, Korea
 | TEL : +82 70 4716 3450 | FAX : +82 70 4716 3456
 | E-MAIL : kosmoent@kosmoent.com | WEB : www.kosmoent.com